



## Liquid Beeswax Wood Finish Technical Specifications

### Ingredients

---

beeswax, shellac wax, carnauba wax, clay, # 115 Xtra Mild Citrus Thinner

### TECHNICAL PROPERTIES:

---

Maintenance and finishing wax with a moderate cleaning effect. Provides a silky, breathable and elastic protection coat. Reduces static loading of surfaces. Does not blister or peel. Easy to refinish by applying additional coats. Wax build-ups and spots can easily be removed with # **115 Xtra Mild Citrus Thinner**.

### MODE OF APPLICATION:

---

Apply one thin coat by cotton cloth, spraying or wax brush. Let dry for at least 2 - 4 hours, then buff surface parallel with the wood grain with a cotton ball, a lambskin disk or a brush.

#### *Note :*

*For initial treatment of floors we recommend using **Carnauba Floor Wax**.*

### DRY TIME :

---

2 - 4 hrs. first coat, 12 hrs. additional coats

### SHELF-LIFE :

---

minimum 2 years, if stored cool and dry. Reseal opened container air-tight.

### COLOURS:

---

clear, transparent

### WHERE TO USE IT:

---

Use indoors only on most types of low-use wooden surfaces, as well as for maintenance of waxed floors. For additional protection, the surface can be pretreated with # **261 Light Linseed Primer Oil** or # 263 Tree Resin & Oil Wood Finish.

**COVERAGE:**

-----

600 sq ft per litre ( quart ) 200-250 sqft. per litre ( quart ) for the first coat and up to 650 sqft per litre ( quart ) for additional coats.

**THINNING & CLEAN UP:**

-----

Product is ready for use and normally does not require any thinning.  
For clean-up use # **115 Eco-House Citrus Thinner**.