



## Light Linseed Primer Oil Technical Specifications

### Ingredients

---

Light purified linseed oil, # 115 Eco-House Citrus Thinner, linseed standoil, leadfree dryers (cobalt & zirconium octoates), herbal essential oils.

### TECHNICAL PROPERTIES:

---

Deep penetrating linseed oil based primer. It creates an elastic and breathable protective coating. Enriches the natural wood grain and dries to a silky finish. Does not blister or peel. Water-repellent, but not permanently water-resistant.

Reduces the tendency for "green" dimensional lumber to crack by slowing, but not inhibiting the drying process.

### MODE OF APPLICATION:

---

Apply liberally by brush, dipping or spraying to achieve thorough saturation. Wipe off unpenetrated primer after approx. 20 - 30 minutes with a cotton cloth. Easy to refinish by applying additional coats.

### DRY TIME :

---

8 - 12 hrs for the 1st coat, 24 hrs for additional coats.

### SHELF-LIFE :

---

min. 3 years, if stored cool and dry. Reseal opened containers air-tight.

### COLOURS:

## Technical Specifications Sheet

-----  
clear transparent to slightly honey-toned ( Gardner 3-4 ).  
May be tinted with suitable stain paste or powdered pigments.

**WHERE TO USE IT:**

---

**Outdoors:**

For priming and conditioning of absorbent surfaces of wood, stone, brick or clay.  
Requires a final weather-resistant finish coating.

**Indoors :**

Same as outdoors, but may also be used as a more economical finish on decorative low-use surfaces, such as furniture, ceilings, wainscoting and other architectural woodwork, which is not frequently exposed to moisture. If used on its own, apply 2-3 coats as desired.

We recommend a finish coat with # 263 Tree Resin & Oil Wood Finish or # **315 Liquid Beeswax Finish**.

**COVERAGE:**

---

90-140 sqft per litre (quart) depending on absorbency rate of the surface.

**THINNING & CLEAN UP:**

---

The product is ready for use and does not require any thinning. Use # **115 Eco-House Citrus Thinner** for clean-up.