



Tree Resin and Oil Wood Finish Technical Specifications

Ingredients

Linseed standoil, pine resin ester, purified linseed oil, # 115 Citrus Thinner, microwax, lead-free driers (cobalt, zirconium, calcium octoates), rosemary oil.

TECHNICAL PROPERTIES:

Deep penetrating vegetable oil & tree resin blend, provides an elastic, breathable protective coating. Water-resistant and surface-hardening. Enriches natural wood grain and does not blister or peel. Food-safe. Easy to refinish by applying additional coat after a light sanding.

MODE OF APPLICATION:

Apply 1 - 3 coats by brush, roller or spraying. Especially the 1st coat should be applied very liberally so that the surface is completely saturated. Wipe off unpenetrated product after 20 - 30 minutes with a clean cotton cloth. Improved protection for floors and furniture can be achieved by an additional treatment with # **300 Carnuba Floor Wax**.

DRY TIME :

8-12 hrs. first coat, 24 hrs. additional coats.

SHELF-LIFE :

2 - 3 years, if stored cool and dry. Reseal opened container air-tight.

DISPOSAL:

Let left-over product dry out until solvent is completely evaporated. Then discard as per local regulations.

COLOURS:

honey-tone clear, tintable

WHERE TO USE IT:

mainly indoors, but may also be used outdoors where UV-protection is not required . This wood is protected against water damage but will turn gray over time from the sun's UV radiation.

COVERAGE:

approx. 80 - 90 sqft. / ltr

THINNING & CLEAN UP:

Ready to use product, for spraying thin with up to 100 % # **115 Citrus Thinner**

CAUTION:

Oil-soaked rags are prone to spontaneous combustion. Always store them safely in an air-tight metal container. **Keep out of reach of children.**